

▲ DECKHAND® DHS

Perfect for use with wheeled excavators in small spaces, the DECKHAND® DHS is an all-purpose excavator attachment that easily adapts to your various job tasks to safely handle and position pipe, poles, casings, drill rod, and more.

- Head unit mounts to any brand of excavator in the 18-23 metric ton class.
- Maximizes maneuverability with 360° continuous rotation, ability to shift loads 5.5 inches in either direction with integrated shift function, and tilt loads up to 24.5°.
- Load locking valves hold load securely, regardless of hydraulic pressure.
- In-cab display allows operator to safely monitor and adjust all functions, working parameters, and hydraulic settings from inside the excavator.
- Requires auxiliary hydraulic circuit on excavator and dedicated case drain line.
- Designed to meet ASME Below-The-Hook Lifting Standards.



DECKHAND® DHS HEAD UNIT

| | |
|---------------------------|---|
| Part Number | 4844 |
| Model Number | DHS |
| Excavator Wt Class | 18-23 METRIC TON |
| Supply Pressure | 3000 PSI / 207 BAR |
| Max Flow | 30 GPM / 114 LPM |
| Min Flow | 20 GPM / 76 LPM |
| Standard Recommended Flow | 25 GPM / 95 LPM |
| Main Beam Size | 6x6 |
| Capacity | 20,000 LB / 9072 KG |
| Weight | 2200 LB / 998 KG |
| Dimensions | 83L x 35W x 49H (IN) / 211L x 89W x 125H (CM) |



www.lavalleyindustries.com