

▲ DECKHAND® DHLT

Purpose-built and optimized for HDD, the DECKHAND®DHLT offers a cost-effective way to safely handle and position pipe, casings, and drill rod. The full-featured DECKHAND®DHLT-SE model includes an electronics package that enables use with most DECKHAND® interchangeable arms.

- Head unit mounts to any brand of excavator in the 20-36 metric ton class.
- Maximizes maneuverability with 360° continuous rotation, ability to shift loads 5.5 inches in either direction with optional shift function, and tilt loads up to 18°.
- Load locking valves hold load securely, regardless of hydraulic pressure.
- In-cab display allows operator to safely monitor and adjust all functions, working parameters, and hydraulic settings from inside the excavator.
- Requires auxiliary hydraulic circuit on excavator and dedicated case drain line.
- Designed to meet ASME Below-The-Hook Lifting Standards.



DECKHAND® DHLT HEAD UNIT

Part Number	8400 / 8470
Model Number	DHLT / DHLT-SE
Excavator Wt Class	20-36 METRIC TON
Supply Pressure	3000 PSI / 207 BAR
Max Flow	30 GPM / 114 LPM
Min Flow	20 GPM / 76 LPM
Standard Recommended Flow	25 GPM / 95 LPM
Main Beam Size	6x6
Capacity	10,000 LB / 4536 KG
Weight	2137 LB / 969 KG
Dimensions	84L x 37W x 54H (IN) / 213L x 94W x 137H (CM)



www.lavalleyindustries.com