

DECKHAND® DHL

Made for the mainline, the DECKHAND®DHL is an all-purpose excavator attachment that easily adapts to your various job tasks to safely handle and position pipe, utility poles, road mats, piles, casings and more. Powerful, secure handling in any condition.

- Head unit mounts to any brand of excavator in the 40-50 metric ton class.
- Maximizes maneuverability with 360° continuous rotation, ability to shift loads 7.5 inches in either direction with integrated shift function, and tilt loads up to 14°.
- Load locking valves hold load securely, regardless of hydraulic pressure.
- In-cab display allows operator to safely monitor and adjust all functions, working parameters, and hydraulic settings from inside the excavator.
- Requires auxiliary hydraulic circuit on excavator and dedicated case drain line.
- Designed to meet ASME Below-The-Hook Lifting Standards.
- Optional stick-mounted camera allows operator to see in even the most difficult spaces.



DECKHAND®DHL HEAD UNIT

Part Number	3000
Model Number	DHL
Excavator Wt Class	40-50 METRIC TON
Supply Pressure	3200 PSI / 221 BAR
Max Flow	40 GPM / 151 LPM
Min Flow	30 GPM / 114 LPM
Standard Recommended Flow	35 GPM / 132 LPM
Main Beam Size	8x8
Capacity	40,000 LB / 18,144 KG
Weight	3650 LB / 1656 KG
Dimensions	112L x 40W x 68H (IN) / 285L x 102W x 173H (CM)



www.lavalleyindustries.com