

▲ DECKHAND® DH4

Strong, safe, and versatile: the DECKHAND® DH4 is an all-purpose excavator attachment that easily adapts to your various job tasks to safely handle and position pipe, poles, road mats, piles, casings, drill rod, and more.

- Head unit mounts to any brand of excavator in the 20-36 metric ton class.
- Maximizes maneuverability with 360° continuous rotation, ability to shift loads 5.5 inches in either direction with integrated shift function, and tilt loads up to 19°.
- Load locking valves hold load securely, regardless of hydraulic pressure.
- In-cab display allows operator to safely monitor and adjust all functions, working parameters, and hydraulic settings from inside the excavator.
- Requires auxiliary hydraulic circuit on excavator and dedicated case drain line.
- Designed to meet ASME Below-The-Hook Lifting Standards.



DECKHAND® DH4 HEAD UNIT

Part Number	3815
Model Number	DH4
Excavator Wt Class	20-36 METRIC TON
Supply Pressure	3000 PSI / 207 BAR
Max Flow	30 GPM / 114 LPM
Min Flow	20 GPM / 76 LPM
Standard Recommended Flow	25 GPM / 95 LPM
Main Beam Size	6x6
Capacity	30,000 LB / 13,608 KG
Weight	2900 LB / 1315 KG
Dimensions	83L x 37W x 63H (IN) / 211L x 94W x 160H (CM)



www.lavalleyindustries.com